

TECHNICAL DETAILS XPA 934

SPECIFICATIONS		
Print specifications	Printing method	Thermal direct / Thermal transfer
	Print resolution	300 dpi / 12 Dot/mm
	Print speed	75–300 mm/s
	Print width max.	106 mm
Label material	Material	Self adhesive label material from 60-160 g/m ² , paper and plastic material (PE, PP, PVC, PA)
	Label roll diameter unwind	max. 300 mm
	Core diameter std.	76,2 mm (3")
	Core diameter opt.	38,1 mm (1.5 ") 101,6 mm (4 ")
	Label width (including backing paper)	20 - 120 mm
Thermal transfer ribbon	Ink side	Inside or outside
	Roll diameter	max. 85 mm
	Run length	600 m
	Width	Max. 110 mm (should be min. 5 mm wider than label width)
Dimensions	H x W x L	620 x 546 x 363 mm
	Weight	27 kg
Power supply	Voltage	100 – 240 V AC
	Frequency	60/50 Hz
Environmental data	Operating temperature	+5 / +40°C
	Humidity	20–85% non-condensing
	Noise	< 72 dB(A)
	Protection Class	IP21
Electronics	Real-time clock	standard
	Control panel	4-key control panel + key for standby 128x64 dot graphical LC-display with RGB color backlight
Data interfaces	Serial	RS-232, D-Sub 9
	USB	2 USB-A host ports (keyboard, scanner, memory stick) 1 USB-B device port (USB2.0)
	Ethernet	10/100/1000 Base-T, RJ-45
	WLAN	optional with USB stick
Signal interfaces	Standard	Basic IO 24V DC, 20W max. output power, PNP 1x M12 4pin for start sensor 1x M12 4pin for outer diameter control sensor for unwinder 1x M12 5pin for 4 status outputs: ready, warning, error, alarm
	Optional	8 IO (Optional IO) Powered via Basic IO, 24V DC, PNP 2x M12 12pin for 4 input and 4 output signals Maximum one 8 IO-boards can be connected
Fonts, barcodes and graphics	Character sets	17 fonts including OCR-A and OCR-B 3 scalable fonts True Type fonts (also unencoded) supported
	Character settings for fixed size fonts	Scaling in X/Y direction up to factor 8, rotation 0°, 90°, 180°, 270°
	Character settings for scalable fonts	Free scaling in X/Y direction, rotation in 1°steps
	Barcodes	1 and 2-dimensional barcodes, scalable in 16 widths and heights
	Graphics formats	BMP, PCX, JPG, TIF, GIF
Options	Unwinder Pro 300 with integrated, internal OD control	
	Product start sensor PNP	
	Signal beacon, 1:1 connection to Basic IO	
	Deviation roller for inside wound material	
	Various label applicators	
	WLAN USB for 1:1 connection	
	ALX 92x replacement kit including mechanical adapter and signal converting box	

The information contained herein is believed to be reliable but NOVEXX Solutions makes no guarantee concerning the accuracy or correctness of the data. The information, like any other, should be confirmed independently for the particular end user conditions to ensure the proposed solution meets the relevant requirements and regulations. © 2020 NOVEXX Solutions GmbH, All rights reserved. Third-party trademarks and/or trade names that may be used herein are the property of their respective owners.